



# Catalogue and order form

### **REQUEST FOR QUOTATION**



### **Portable Earthing Device Sets**

Required earthing device configuration															
						118									
									111						
Junction															
Ů E		ŮE					ÓΕ		ÓΕ		ΣE	ÓΕ			
3-phase with junction block, single earth		Single phase earth		2-phase bonder ( jumper)		(aka	3-phase with separate earth lead		3-phase with linked earth lead		earth	3-phase with centre attached earth lead			
Qty:		Qty:	Qty:				Qty:			Qty:			Qty:		
Required fault current (kA)			_												
☐ 6kA/1s	3		□ 1	0kA/1s		☐ 16kA/1s						☐ 25kA/1s			
Preferred <b>cable</b> cro	ss se	ctional area an	d material												
☐ 25mm2 CU			□ 35mm2 CU			□ 50mm2 CU □ 70m			mm2 AL		☐ 147mm2 AL				
☐ Line cable		☐ Line cable			☐ Line cable ☐ Lir			ne cable			☐ Line cable				
☐ Phase to Phas		☐ Phase to Phase						hase to Phase			☐ Phase to Phase ☐ Phase to earth				
☐ Phase to earth  Cable length require			hase to earth			☐ Phase to earth ☐ Pha			nase to earth		☐ Phase to earth				
Cable length require	,														
		Phase to Junction (P-J)													
O N	(m)				Phase to phase						Phase to Earth				
Junction		Junction to Ear			m						m				
<sup>7-E(M)</sup> '			m							ĠΕ					
Required Clamps	ı													1	
						1									11
Line Clamp 55 Jaw opening max 55mm	Snap-on Clamp Jaw opening max 25mm		Line Clamp 38 Jaw opening max 38m		mm	Line Clamp 80 Jaw opening max 80mm			Ground Clamp 15 Jaw opening max 15mm		Jaw op	Ground Clamp 42 Jaw opening max 42mm		Jaw c	nd Clamp 27 opening max 27mm
☐ Line/head		☐ Line/head ☐ Line/h		ead		☐ Line/head			☐ Line/head		☐ Line/head			☐ Line	
☐ Ground/tail			☐ Ground/				Ground/tail ☐ Ground/tai					☐ Ground/tail			
Required Clamp Sp	indle													•	
Ŧ		Ī					(of								
☐ Bayonet		☐ Screwdriver		☐ T-Handle			☐ Flexihead		ead	☐ Pole Handle		Э	☐ Pfisterer Bayon		er Bayonet
☐ Line/head		☐ Line/head		☐ Line	☐ Line/head		☐ Line/head		☐ Line/head			☐ Line/head			
☐ Ground/tail		☐ Ground/tail ☐ Gr		Ground/tail		☐ Ground/tail		☐ Ground/tail			☐ Ground/tail				
Name:			Company:												
Mobile:				Phone:						O. T.	TO THE REAL PROPERTY.	ACCOST	HATTER TO		
Email:		Date:		ite:	Click or tap to enter a date.						1				
Address:				L		1					□ Bag requ	red		Qty: _	
Notes:										1					

## **REQUEST FOR QUOTATION**



#### Components

			1			
Line Clamp 55 Jaw opening max 55mm	Snap-on Clamp Jaw opening max 25mm	Line Clamp 38 Jaw opening max 38mm	Line Clamp 80 Jaw opening max 80mm	Ground Clamp 15 Jaw opening max 15mm	Ground Clamp 42 Jaw opening max 42mm	Ground Clamp 27 Jaw opening max 27mm
☐ Bayonet ☐ Screwdriver ☐ T-Handle ☐ Flexihead ☐ Pole handle ☐ Pfisterer bayonet	☐ Bayonet ☐ Screwdriver ☐ T-Handle ☐ Flexihead ☐ Pole handle ☐ Pfisterer bayonet	☐ Bayonet ☐ Screwdriver ☐ T-Handle ☐ Flexihead ☐ Pole handle ☐ Pfisterer bayonet	□ Bayonet □ Screwdriver □ T-Handle □ Flexihead □ Pole handle □ Pfisterer bayonet	☐ T-Handle ☐ Screwdriver	☐ T-Handle ☐ Screwdriver	☐ Bayonet ☐ Screwdriver ☐ T-Handle ☐ Pole handle
Qty:	Qty:	Qty:	Qty:	Qty:	Qty:	Qty:
	O O O O O O O O O O O O O O O O O O O	The state of the s			Copper Cable	Aluminium
Operating pole extension	Operating pole handle	Operating pole top section	Lugs	Heatshrink	☐ 25mm2 ☐ 35mm2 ☐ 50mm2	Cable  70mm2  147mm2
Qty:	Qty:	Qty:	Qty:	Colour:	Qty:	Qty:
Length: m	Length: m	Length: m	Size: mm	Length: m	Length: m	Length: m
			}	-		
Sofamel VTE Voltage Detector  5-36kV 5-66kV 66-220kV	SEW 375HP Voltage Detector 240V-275kV AC	RIVclip Comes in bags of 100	DDO Fuse Cartridge Holder	Galvanised Earth Spike □ 760mm □ 900mm	Bronze Auger 800mm	Snap-On Applicator
Qty:, min 4	Qty:	Qty:bags	Qty:	Qty:	Qty:	Qty:
			37			
Earthing Stud Belt Sander	Earthing Stud Sander	Various Adapters Specify in Notes	Twist-On Stay Guard Comes in packs of 20	Bayonet Adapter with fixed handle	Bayonet Adapter with Button Joint	Bayonet to Universal Sunrise Adapter
Qty:	Qty:	Qty:	Qty:packs	Qty:	Qty:	Qty:
		Salar			With Button Joint	
Transmission Cluster Bar	Distribution Cluster Bar	Orange spiral	Equipotential Breakaway Bond	LV Disconnect for NZI Porcelain Fuses	150mm Handle End Color:	Junction block  5-way (50mm2)  6-way (25/35mm2)
Qty:	Qty:	Length: m	Qty:	Qty:	Qty:	Qty:

### **REQUEST FOR QUOTATION**






BETACOM EARTHING is a specialist manufacturer of Portable Earthing Devices (PEDs) for both distribution and transmission applications. Our products are sold and supported throughout Australia, New Zealand and the Pacific Rim.

#### Our products include:

- Temporary earthing sets and assemblies for specified fault levels for: Transmission and distribution applications; Substation
  applications.
- Cluster bars for both distribution and transmission applications (for wood and poles).
- Equipotential bonding assemblies, jumpers and wood pole equipotential spikes.
- Our selection of line & earth clamps covers all identified practicable requirements.
- Associated auxiliary equipment, including earthing augers, lifting devices, earthing studs and dedicated substation earthing terminals.
- Other safety equipment products including HV operating poles and adaptors / attachments.

All Betacom PEDs and equipment are type tested to **IEC 61230** or otherwise manufactured to specific customer design specifications.

Portable Earthing Devices save lives, they are the Line Operator's last defence when working on a conductor that unexpectedly becomes live. Betacom has been the leading manufacturer of PEDs in New Zealand since 1969.





Quality ISO 9001

Portable Earthing Device	Tested To:	Portable Earthing Device	Tested To:	Portable Earthing Device	Tested To:
25mm2 CU	8.5kA for 0.5s 6kA for 1s	50mm2 CU	22.6kA for 0.5s 16kA for 1s	70mm2 AL	16kA for 0.5s 11.3kA for 1s
35mm2 CU	14.1kA for 0.5s 10kA for 1s			147mm2 AL	35.4kA for 0.5s 25kA for 1s