

Grip-All Telescoping 5 ft 11 in to 8 ft 4 in (1.8 to 2.5 m) with Universal Head



By CHANCE Lineman Grade Tools

Catalog # [C4033060](#)

GRIPALL-TELESCOPING 5FT10.5IN-8FT 3.75IN, The most versatile tool in a lineworker's hands, the Grip-All stick puts an easy-to-control "finger" on an insulated pole. Although primarily designed for installing hot-line and grounding clamps, it serves both overhead and underground circuits with various end fittings. Commonly called a "shotgun," the operating mechanism incorporates a sliding hand grip that opens the hook to grasp a clamp eyescrew and retract it into the tool head. A thumb latch then must be depressed to release the locked hand grip so it can open the hook. While the tool head is of Lexan® for close-quarter operations, the worker must maintain recommended working distance solely on the Epoxyglas® pole section of the handle as the hook and its actuator are metal parts. Easy to care for, Grip-All sticks do not require field stripping to clean. All insulated parts including the operating rod are outside the main pole, readily accessible to wipe dry. CAUTION: Do not clean the plastic head with solvent.

Features

- Tested per OSHA & ASTM F711
- Available in two sizes, each readily locks at variable working lengths
- Design features rotating coupler and an engineered positive-lock button with safety stop to keep sections from parting or hook releasing while in use
- Mechanism locks sections into a solid, rattle-free tool
- Black head makes it obvious head is not included in minimum approach distance
- Can replace several conventional clampsticks
- Allows linemen to adhere to safe-working distances and positioning needs, with fewer sticks
- Reduces the number of clampsticks required on a line truck, saving limited storage space
- Engineered interface between sections ensure tool retracts with full control
- Close fit helps keep out dirt and moisture
- Top section is made with foam-center Epoxyglas® insulated pole
- Functions of this telescoping style are identical to fixed-length style
- All controls can be easily accessed while wearing gloves
- Easy to disassemble, stick must be kept clean and dry inside to ensure long life
- T4031245 Button and Spring Replacement Kit

General

Catalog Number	C4033060
EU RoHS Indicator	No
Storage Bag Included?	P643-6 (Bag not included. Must be ordered separately.)
Style	Telescoping Style with Universal Fitting on Handle
UPC	096359020332

Dimensions

Dimensions	96 in x 4.5 in x 4.5 in
Dimensions Metric	243.8 mm x 11.4 mm x 11.4 mm
Height	4.5 in
Height Metric	11.4 mm
Length	96 in
Length - Retracted	71 in
Length - Retracted Metric	1.6 m
Length Metric	243.8 mm
Weight	10.5 lb
Weight Metric	4.8 kg
Width	4.5 in
Width Metric	11.4 mm

Certifications And Compliance

Buy America(n) Qualified	TAA Compliant (All status valid till December 2024)
--------------------------	-----------------------------------------------------

Product Assets

Catalogs - Insulated Hand Tools
Installation Manuals - CHANCE® Epoxiglas™ Live-Line Tool
Instruction Manual

Sales Drawings - Telescoping Gripal
Specifications - C4033060



A Hubbell brand

©2025 Hubbell Incorporated. All rights reserved
CLTE-C4033060-SPEC-EN | REV 7/2025